

Model: 40611



Two Handle Kitchen Faucet

DESCRIPTION

- Metal construction with chrome plated finish
- 1/2" IPS connections
- Six (6) individual boxes per master carton
- Handles withstand aggressive scrubbing cleaners

OPERATION

- Lever style handle
- **Hot side:** Turn counterclockwise to open (clockwise to close)
- **Cold side:** Turn clockwise to open (counterclockwise to close)
- Will operate with less than 5 lbs. of torque
- No grasping motion required to operate the faucet handles

FLOW

- Spout flow limited to 2.0 gpm (7.6 L/min) at 60 psi

CARTRIDGE

- Ceramic disc technology
- Non-metallic, non-ferrous, and brass material
- Single body construction for easy replacement

STANDARDS

- Third party certified to ASME A112.18.1/ CSA B125.1, ANSI/NSF 61/9 and all applicable requirements referenced therein, the Federal Safe Drinking Water Act, California Proposition 65, Illinois, Massachusetts, and Texas
- All CFG products are compliant to all plumbing codes that require 3rd party certification to the applicable plumbing/fitting standards
- Features red/blue hot/cold temperature indicators

WARRANTY – RESIDENTIAL, COMMERCIAL

- Ten year limited warranty against defects in materials and manufacturing workmanship
- Refer to the installation instructions enclosed with each CFG product or call 1-888-450-4910 for complete warranty information

The use of aerator part 116711 reduces flow to a maximum of 1.5 gpm (5.7L/min.)